

	VIRYA-1	VIRYA-0.98 + -1.04	VIRYA-1.36	VIRYA-1.66	VIRYA-1.81
Rotor diameter	D = 1 m	D = 0.98, 1.04 m	D = 1.36 m	D = 1.66 m	D = 1.81 m
Number of blades	B = 2	B = 3	B = 2	B = 3	B = 2
Design tip speed ratio	$\lambda_d = 4.25$	$\lambda_d = 3, 3.5$	$\lambda_d = 5$	$\lambda_d = 4.5$	$\lambda_d = 5$
Generator	axial flux 8-pole, 3-phase	hub dynamo 28-pole, 1-phase	axial flux 8-pole, 3-phase	axial flux 12-pole, 3-phase	axial flux 8-pole, 3-phase
Material rotor blades	aluminium	aluminium	stainless steel	stainless steel	stainless steel
Material head	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel
Material and thickness vane blade	aluminium 1.5 mm	aluminium 1.5 mm	aluminium 2 mm	aluminium 2 mm	stainless steel 1 mm
Gear ratio	i = 1	i = 1	i = 1	i = 1	i = 1
Rotor eccentricity	e = 0.09 m	e = 0.09 m	e = 0.12 m	e = 0.15 m	e = 0.15 m
Height tower pipe	H = 1 m	H = 1 m	H = 2 m	H = 2 m	H = 2 m
Total tower height	H _{tot} = 3.7 m	H _{tot} = 3.7 m	H _{tot} = 4.7 m	H _{tot} = 4.7 m	H _{tot} = 7.5 m
Number of legs and material lower tower part	one square wooden pole	one square wooden pole	one square wooden pole	one square wooden pole	free standing tubular tower
Mass with tower pipe only	m = 4.8 kg	m = 4.85 kg	m = 13.6 kg	m = 22 kg	m = 25 kg
Starting wind speed	V _{start} = 2 m/s	V _{start} = 2.6 m/s	V _{start} = 2.4 m/s	V _{start} = 2.3 m/s	V _{start} = 2.6 m/s
Cut in wind speed (if started)	V _{cut in} = 2.5 m/s	V _{cut in} = 2 m/s	V _{cut in} = 2.5 m/s	V _{cut in} = 3 m/s	V _{cut in} = 3 m/s
Rated wind speed	V _{rated} = 8 m/s	V _{rated} = 8 m/s	V _{rated} = 9 m/s	V _{rated} = 9 m/s	V _{rated} = 11 m/s
Survival wind speed	V _{surv} = 30 m/s	V _{surv} = 30 m/s	V _{surv} = 30 m/s	V _{surv} = 30 m/s	V _{surv} = 35 m/s
Nominal battery voltage	U = 12 V DC	U = 12 V DC	U = 12 V DC	U = 12 V DC	U = 12 or 24 V DC
Rectification generator	3-phase star	1-phase	3-phase star	3-phase star	3-phase star
Power at rated wind speed	P _{rated} = 27 W	P _{rated} = 6 W	P _{rated} = 71 W	P _{rated} = 130 W	P _{rated} = 206 W
Report rotor calculations	KD 679	KD 615 + 518	KD 571	KD 596	KD 631
Generator measurements	in KD 678	in KD 518	in KD 571	not yet performed	not yet performed
Licence fee excluding VAT	free via website	free via website	free via website	free via website	free via website

table 1 VIRYA windmills with hub dynamo or axial flux generator. For manual and drawings VIRYA-1.04, -1.36, -1.66 and -1.81 see website menu KD-reports at the bottom. For drawings VIRYA-1 see report KD 579. For drawings VIRYA-0.98 see report KD 615.

	VIRYA-1.02	VIRYA-1.75W	VIRYA-1.8W	VIRYA-2.22
Rotor diameter	D = 1.02 m	D = 1.75 m	D = 1.8 m	D = 2.22 m
Number of blades	B = 3	B = 2	B = 2	B = 2
Design tip speed ratio	$\lambda_d = 3.5$	$\lambda_d = 7$	$\lambda_d = 6.25$	$\lambda_d = 5$
Generator	axial flux, steel stator sheet 8-pole, 3-phase	Hefei Top Grand TGET165- 0.15KW-500R	radial flux, iron free stator 8-pole, 3-phase	Hefei Top Grand TGET260- 0.5KW-350R
Material rotor blades	stainless steel	hard wood	ply wood	stainless steel
Material head	stainless steel	stainless steel	stainless steel	stainless steel
Material and thickness vane blade	aluminium 1.5 mm	aluminium 2 mm	stainless steel 1 mm	stainless steel 1 mm
Gear ratio	i = 1	i = 1	i = 1	i = 1
Rotor eccentricity	e = 0.09 m	e = 0.15 m	e = 0.15 m	e = 0.18 m
Height tower pipe	H = 1 m	H = 2 m	H = 2 m	H = 2 m
Total tower height	H _{tot} = 3.7 m	H _{tot} = 7.8 m	H _{tot} = 7.8 m	H _{tot} = 7.5 m
Number of legs and material lower tower part	wooden pole	free standing tubular tower	free standing tubular tower	free standing 4-legs angle iron
Mass with tower pipe only	m = 5.6 kg	m = 19 kg	m = 22 kg	m = 35 kg
Starting wind speed	V _{start} = 1.5 m/s	V _{start} = 3.2 m/s	V _{start} = 2.3 m/s	V _{start} = 2.4 m/s
Cut in wind speed (if started)	V _{cut in} = 2.7 m/s	V _{cut in} = 2.8 m/s	V _{cut in} = 2.6 m/s	V _{cut in} = 2.5 m/s
Rated wind speed	V _{rated} = 8 m/s	V _{rated} = 9 m/s	V _{rated} = 11 m/s	V _{rated} = 10 m/s
Survival wind speed	V _{surv} = 30 m/s	V _{surv} = 35 m/s	V _{surv} = 35 m/s	V _{surv} = 35 m/s
Nominal battery voltage	U = 12 V DC	U = 12 V DC	U = 24 V DC	U = 24 V DC
Rectification generator	3-phase star	3-phase star	3-phase star	3-phase star
Power at rated wind speed	P _{rated} = 24 W	P _{rated} = 150 W	P _{rated} = 230 W	P _{rated} = 350 W
Report rotor calculations	KD 678	KD 669	KD 664	KD 676
Generator measurements	in KD 678	in KD 595	not yet performed	not yet performed
Licence fee excluding VAT	free via website	free via website	free via website	free via website

table 2 VIRYA windmills with an axial flux generator or a radial flux generator with no iron in the stator. The drawings of the rotor are given in the report with the rotor calculations. For generator drawings, see rotor report. The drawings of the head and the tower of the VIRYA-1.75W and the VIRYA-1.8W are given in the manual of the VIRYA-1.81.